

AMENDMENTS TO THE CLAIMS

1. (Previously Presented) An authentication method for network security, comprising the following steps:

configuring a Media Gateway (MG) with an authentication key and setting a security data package on a network protocol, by a Media Gateway Controller (MGC);

during a security authentication, sending, by the MGC, security authentication request data to the MG using the data package;

receiving by the MGC a calculation result obtained by performing an encryption calculation on the request data using the authentication key by the MG; and

determining by the MGC whether the MG is legal according to the calculation result.

2. (Original) The authentication method for network security according to claim 1, wherein said network protocol is Media Gateway Control Protocol (MGCP).

3. (Original) The authentication method for network security according to claim 1, wherein said network protocol is H248 protocol.

4. (Previously Presented) The authentication method for network security according to claim 1, wherein said data package comprises a security authentication request signal and a security authentication completion event, said security authentication request signal comprising a security authentication parameter, and said security authentication completion event comprising a security authentication result parameter.

5. (Previously Presented) The authentication method for network security according to claim 4, wherein the step of sending security authentication request data from the MGC to the MG using the data package further comprises:

sending the security authentication request signal in the data package to the MG.

6. (Previously Presented) The authentication method for network security according to claim 5, wherein the receiving step comprises:

receiving the calculated result through the security authentication result parameter in the security authentication completion event in the data package, wherein the calculation result is obtained by performing an encryption calculation on the security authentication parameter using the authentication key by the MG.